

**PRODUCT NAME****H-Go HDT Fluid****TECHNICAL DATA****INTRODUCTION**

H-Go HDT Fluid is a high-quality universal lubricant for tractors, specifically developed for the new generation of equipment with CVT-type transmissions, but also suitable for equipment with traditional transmissions. It is formulated with high-viscosity index base oils to which a carefully selected set of additives have been added to provide maximum protection against metal wear, excellent resistance to oxidation, and rust. Additionally, particular attention has been given to shear stability.

APPLICATIONS

H-Go HDT Fluid is specially formulated for tractors using a single fluid for hydraulic systems, hydrostatic and power-assisted transmissions, differential, clutch, and oil-immersed brakes. It is suitable for all brands of tractors used for agricultural and industrial purposes where the manufacturer recommends a universal fluid. Not suitable for automotive CVT transmissions.

GEAR OIL EP TYPICAL PROPERTIES**MEETS THE SPECIFICATIONS OF**

AGCO	M-1145, White Q-1826
Allison	C-4
API	GL-4
Case New Holland	MAT 3505, MAT3540
Caterpillar	TO-2
Eaton / Vickers	M-2950-S, 1-286-S
John Deere	J20C
Kubota	UDT
Parker/ Volvo	WB 101
ZF	TE-ML 03E, TE-ML 05F, TE-ML 06K, TE-ML 17E, TE-ML 21F
Denison	HF-0, HF-1, HF-2

SPECIFICATIONS**VALUES**

Viscosity, ASTM D 7042 cSt 40 °C cSt 100 °C	60 9,5
Viscosity index, ASTM D 2270	141
Pour point °C, ASTM D 5950,	-42
KRL 20 Hr, cSt CEC L-45-A-99 ASTM D445	141
Viscosity Brookfield, cP à -20°C ASTM D 2983	3500
Colour	Amber