

SECTION 1 Identification

1.1. GHS Product identifier

Product form : Mixture
Product name : Plumbing antifreeze

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

No additional information available

1.4. Supplier's details

Harnois Énergies
80 Route 158
Saint-Thomas, Qc J0K 3L0
Canada
T 450-759-7979; Sans frais: 1-800-363-2712 - F 450-759-7001

1.5. Emergency phone number

Emergency number : Harnois Énergies Customer Service: 1-800-363-2712 (Monday to Friday 7 a.m. to 8 p.m.)

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Flammable liquids, Category 3	H226	Flammable liquid and vapour
Serious eye damage/eye irritation, Category 2A	H319	Causes serious eye irritation
Full text of H-statements: see section 16		

2.2. GHS label elements, including precautionary statements

GHS CA labelling

Hazard pictograms :  

Signal word : Warning

Hazard statements : H226 - Flammable liquid and vapour
H319 - Causes serious eye irritation

Precautionary statements : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P264 - Wash hands, forearms and face thoroughly after handling.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.

Plumbing antifreeze

Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P370+P378 - In case of fire: Use appropriate media to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)
Ethanol	-	CAS-No.: 64-17-5	10 – 40

Full text of hazard classes and H-statements : see section 16

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.
First-aid measures general : If you feel unwell, seek medical advice.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation : None under normal conditions.
Symptoms/effects after skin contact : None under normal conditions.
Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : None under normal conditions.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5 Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

Plumbing antifreeze

Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)

5.2. Specific hazards arising from the chemical

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	---

Environmental precautions	: Avoid release to the environment.
---------------------------	-------------------------------------

6.2. Methods and materials for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed.
Packaging materials	: Store always product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Plumbing antifreeze

Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)

Ethanol (64-17-5)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Ethanol (Ethyl alcohol)
OEL TWA	1880 mg/m ³
	1000 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Ethyl alcohol (Ethanol)
VECD (OEL STEV)	1000 ppm
Notations and remarks	C3
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Ethanol
OEL STEL	1000 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Ethanol
OEL STEL	1880 mg/m ³
	1000 ppm
Notations and remarks	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Ethanol
OEL STEL	1000 ppm
Notations and remarks	URT irr
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Ethanol
OEL STEL	1880 mg/m ³
	1000 ppm
Notations and remarks	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Ethanol
OEL STEL	1880 mg/m ³
	1000 ppm
Notations and remarks	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)

Plumbing antifreeze

Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)

Ethanol (64-17-5)	
Regulatory reference	ACGIH 2025
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Ethanol
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Ethanol
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Ethanol
OEL TWAEV	1000 ppm
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Ethanol
OEL STEL	1880 mg/m ³
	1000 ppm
Notations and remarks	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Ethanol
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Protective gloves

Plumbing antifreeze

Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)

Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Pink
Odour	: Alcohol
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 35 °C (95°F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

Reactivity	: Flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: No additional information available

Plumbing antifreeze

Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)

Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Ethanol (64-17-5)	
LD50 oral rat	15010 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 14450 - 15560
LD50 oral	8300 mg/kg bodyweight Animal: mouse
LC50 Inhalation - Rat (Vapours)	116.9 mg/l Source: ECHA
ATE CA (oral)	8300 mg/kg bodyweight
ATE CA (vapours)	116.9 mg/l/4h

Skin corrosion/irritation	: Not classified
---------------------------	------------------

Ethanol (64-17-5)	
pH	7 Source: chemicalbook

Serious eye damage/irritation	: Causes serious eye irritation.
-------------------------------	----------------------------------

Ethanol (64-17-5)	
pH	7 Source: chemicalbook

Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Ethanol (64-17-5)	
IARC group	1 - Carcinogenic to humans

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

Ethanol (64-17-5)	
NOAEL (subchronic, oral, animal/male, 90 days)	< 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (subchronic, oral, animal/female, 90 days)	> 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)

Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

Plumbing antifreeze

Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)

SECTION 12 Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Ethanol (64-17-5)	
LC50 - Fish [1]	14.2 g/l Test organisms (species): Pimephales promelas
ErC50 algae	275 mg/l Source: ECHA
NOEC (chronic)	9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'

12.2. Persistence and degradability

Plumbing antifreeze	
Persistence and degradability	Not rapidly degradable
Ethanol (64-17-5)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

Ethanol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	-0.32 Source: ICSC

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapours may accumulate in the container. Do not re-use empty containers.

SECTION 14 Transport information

In accordance with TDG / IMDG / IATA

14.1. UN Number

UN-No. (TDG)	: UN1170
UN-No. (IMDG)	: 1170
UN-No. (IATA)	: 1170

Plumbing antifreeze

Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)

14.2. UN Proper Shipping Name

Proper Shipping Name (TDG)	: ETHANOL SOLUTION
Proper Shipping Name (IMDG)	: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
Proper Shipping Name (IATA)	: Ethanol solution

14.3. Transport hazard class(es)

TDG

Transport hazard class(es) (TDG)	: 3
Hazard labels (TDG)	: 3
	:



IMDG

Transport hazard class(es) (IMDG)	: 3
Danger labels (IMDG)	: 3
	:



IATA

Transport hazard class(es) (IATA)	: 3
Danger labels (IATA)	: 3
	:



14.4. Packing group, if applicable

Packing group (TDG)	: II
Packing group (IMDG)	: II
Packing group (IATA)	: II

14.5. Environmental hazards

Dangerous for the environment	: No
Other information	: No supplementary information available.

14.6. Special precautions for user

TDG

UN-No. (TDG)	: UN1170
TDG Special Provisions	: 150 - An approved ERAP is required for the dangerous goods referred to in paragraph 7.2(1)(f) of Part 7 (Emergency Response Assistance Plan).
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E2
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 5 L
Emergency Response Guide (ERG) Number	: 127

IMDG

Special provisions (IMDG)	: 144
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2

Plumbing antifreeze

Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)

Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Colourless, volatile liquids. Pure ETHANOL: flashpoint 13°C c.c. Explosive limits: 3.3% to 19%. Miscible with water.

IATA

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3, A58, A180
ERG code (IATA)	: 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78⁹ and the IBC Code¹⁰

Not applicable

SECTION 15 Regulatory information

Ethanol (64-17-5)
Listed on the Canadian DSL (Domestic Substances List)

SECTION 16 Other Information

Issue date	: 5/15/2019
Revision date	: 9/23/2025
Supersedes	: 5/15/2019

Full text of hazard classes and H-statements:	
H226	Flammable liquid and vapour
H319	Causes serious eye irritation

Safety Data Sheet (SDS), Canada - Toxyscan 2025

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.